

X-Marker Warning Signal (Part #WTSM27-FX)



The X-Marker warning signal is an effective and efficient means for warning pilots of closed airport runways and taxiways. The warning signal also protects maintenance crews working in these areas. The X-Marker exceeds FAA guidelines for shape configuration, providing highly visible lights on outstretched arms 27-feet long. Easy to reposition, the X-Marker quickly folds up for transport or storage.

Features:

- Exceeds FAA guidelines.
- Extremely portable, can be towed by most trucks.
- Standard 2-inch ball coupler tow-hitch.
- Rapid deployment and easy set up.
- Either vertical or horizontal coverage.
- 20 sealed-beam amber lights for nighttime and adverse weather.
- 12 sealed-beam white lights for daytime.
- Two independent power circuits to increase reliability.
- Lockable control box and engine cage.
- Lombardini air-cooled diesel engine with 30-gallon fuel tank.
- Up to 160 hours of continuous operation.

Deployment:

- *Stability Outriggers:* Telescoping design, 123" (3.12 m) span at full extension.
- *Arm-Frame Adjustability:* 105% total pivot angle, adjustable in 5-degree increments.
- *Hand-Winch:* 1500 lb. capacity, friction safety brake, 1/4" galvanized 7x19 aircraft cable.
- *Spring Tilt:* Leaf spring tilts arm-frame assembly off vertical position.

TRAVELING LENGTH:

Single: 26' 5" / 8.08 m

Tandem: 42' 5" / 12.95 m

OPERATING LENGTH:

21' / 6.40 m

TRAVELING HEIGHT:

12' 5" / 3.81 m

OPERATING HEIGHT:

21' / 6.4 m

ARM LENGTH:

27' / 8.23 m

X-SHAPE (square):

19' 1" / 5.82 m

TRAILER WIDTH:

8' / 2.44 m

